



Declaration of Performance

DoP-CPR- 17-3455

1. Unique identification code of the product, product type or product family: Collection: Oculaire Type: 02 Designs: Articles: Metric, Insignia, 80500-80506, 80550-80556, Unite, Combine, 80600-80606, 80650-80656, Line 80700-80712																																					
2. Identification of the product: Type, batch or serial number: See packing label																																					
3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15102:2007+A1:2011: Wallcovering for decorative use																																					
4. Name and contact address of the manufacturer: <div style="float:right; text-align: right;"> Arte NV Industriezone "De Waerde" Senator A. Jeurissenlaan 1210 BE-3520 Zonhoven T +32 (0) 11 81 93 00 F +32 (0) 11 81 93 01 info.belgium@arte-international.com </div>																																					
5. Name and contact address of authorised representative (distributor, importer): Not applicable																																					
6. System of assessment and verification of constancy of performance: System 3																																					
7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s): Certification report Centexbel : 19/745																																					
8. Declared performance: <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:25%;">Essential Characteristic</th> <th style="width:25%;">Performance</th> <th style="width:10%;">Harmonised technical specification</th> <th style="width:25%;">Essential Characteristic</th> <th style="width:10%;">Performance</th> <th style="width:15%;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td>B-S1,d0</td> <td rowspan="8" style="text-align:center; vertical-align:middle;">EN 15102:2007 A1:2011</td> <td>Release of vinyl chloride monomer EN 12149-B</td> <td style="text-align:center;">< 0.2 mg/kg</td> <td rowspan="4" style="text-align:center; vertical-align:middle;">EN 15102:2007 A1: 2011</td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td style="text-align:center;">< 120 mg / kg</td> <td rowspan="3" style="text-align:center; vertical-align:middle;">Sound absorption ISO 354</td> <td style="text-align:center;">NPD</td> </tr> <tr> <td rowspan="5">Release of heavy metals (EN 12149-A)</td> <td>Anitimony < 0.1 mg/kg</td> <td rowspan="5" style="text-align:center; vertical-align:middle;">Thermal resistance "EN 12524" or "EN12667"</td> <td style="text-align:center;">NPD</td> </tr> <tr> <td>Arcenic < 0.1 mg/kg</td> </tr> <tr> <td>Barium < 0.1 mg/kg</td> </tr> <tr> <td>Cadmium < 0.3 mg/kg</td> </tr> <tr> <td>Chromium < 0.1 mg/kg</td> </tr> <tr> <td>Lead < 0.5 mg/kg</td> <td style="text-align:center;">NPD</td> </tr> <tr> <td>Mercury < 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Selenium < 1.0 mg/kg</td> <td></td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification	Reaction to fire EN 13501-1	B-S1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg	Sound absorption ISO 354	NPD	Release of heavy metals (EN 12149-A)	Anitimony < 0.1 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD	Arcenic < 0.1 mg/kg	Barium < 0.1 mg/kg	Cadmium < 0.3 mg/kg	Chromium < 0.1 mg/kg	Lead < 0.5 mg/kg	NPD	Mercury < 0.1 mg/kg			Selenium < 1.0 mg/kg		
Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification																																
Reaction to fire EN 13501-1	B-S1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																																
Release of formaldehyde EN 12149-C	< 120 mg / kg		Sound absorption ISO 354	NPD																																	
Release of heavy metals (EN 12149-A)	Anitimony < 0.1 mg/kg			Thermal resistance "EN 12524" or "EN12667"		NPD																															
	Arcenic < 0.1 mg/kg																																				
	Barium < 0.1 mg/kg																																				
	Cadmium < 0.3 mg/kg																																				
	Chromium < 0.1 mg/kg																																				
Lead < 0.5 mg/kg	NPD																																				
Mercury < 0.1 mg/kg																																					
Selenium < 1.0 mg/kg																																					
* NPD: No Performance Declared																																					
Signed for and behalf of the manufacturer or authorised representative by: <div style="text-align:right; margin-top: 20px;"> </div>																																					
29-Jan-20		Philippe Desart		Managing Director																																	