



# Declaration of Performance

DoP-CPR- 19-3595

<b>1. Unique identification code of the product, product type or product family:</b> <b>Collection:</b> Timber <span style="float:right"><b>Type:</b> 02</span>  <b>Designs:</b> <span style="float:right"><b>Articles:</b></span> Formation, <span style="float:right">38200-38204,</span> Trapeze, <span style="float:right">38210-38215,</span> Grain, <span style="float:right">38220-38231,</span> Elements <span style="float:right">38240-38244</span>																																			
<b>2. Identification of the product:</b> <b>Type, batch or serial number:</b> See packing label																																			
<b>3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15102:2007+A1:2011: Wallcovering for decorative use</b>																																			
<b>4. Name and contact address of the manufacturer:</b> <div style="float:right; text-align:left;">                 Arte NV                  Industriezone "De Waerde"                  Senator A. Jeurissenlaan 1210                  BE-3520 Zonhoven                  T +32 (0) 11 81 93 00                  F +32 (0) 11 81 93 01                  info.belgium@arte-international.com             </div>																																			
<b>5. Name and contact address of authorised representative (distributor, importer):</b> Not applicable																																			
<b>6. System of assessment and verification of constancy of performance:</b> System 3																																			
<b>7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s):</b>  Certification report Centexbel : 19/745																																			
<b>8. Declared performance:</b> <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width:25%;">Essential Characteristic</th> <th style="width:25%;">Performance</th> <th style="width:10%;">Harmonised technical specification</th> <th style="width:25%;">Essential Characteristic</th> <th style="width:10%;">Performance</th> <th style="width:15%;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td><b>B-S1,d0</b></td> <td rowspan="8" style="text-align:center; vertical-align:middle;">EN 15102:2007 A1:2011</td> <td>Release of vinyl chloride monomer EN 12149-B</td> <td>&lt; 0.2 mg/kg</td> <td rowspan="4" style="text-align:center; vertical-align:middle;">EN 15102:2007 A1: 2011</td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td>&lt; 120 mg / kg</td> <td rowspan="3">Sound absorption ISO 354</td> <td>NPD</td> </tr> <tr> <td rowspan="5">Release of heavy metals (EN 12149-A)</td> <td>Anitimony &lt; 0.1 mg/kg</td> <td rowspan="5">Thermal resistance "EN 12524" or "EN12667"</td> <td>NPD</td> </tr> <tr> <td>Arcenic &lt; 0.1 mg/kg</td> </tr> <tr> <td>Barium &lt; 0.1 mg/kg</td> </tr> <tr> <td>Cadmium &lt; 0.3 mg/kg</td> </tr> <tr> <td>Chromium &lt; 0.1 mg/kg</td> </tr> <tr> <td>Lead &lt; 0.5 mg/kg</td> <td></td> </tr> <tr> <td>Mercury &lt; 0.1 mg/kg</td> <td></td> </tr> <tr> <td>Selenium &lt; 1.0 mg/kg</td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification	Reaction to fire EN 13501-1	<b>B-S1,d0</b>	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg	Sound absorption ISO 354	NPD	Release of heavy metals (EN 12149-A)	Anitimony < 0.1 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD	Arcenic < 0.1 mg/kg	Barium < 0.1 mg/kg	Cadmium < 0.3 mg/kg	Chromium < 0.1 mg/kg	Lead < 0.5 mg/kg		Mercury < 0.1 mg/kg		Selenium < 1.0 mg/kg	
Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification																														
Reaction to fire EN 13501-1	<b>B-S1,d0</b>	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																														
Release of formaldehyde EN 12149-C	< 120 mg / kg		Sound absorption ISO 354	NPD																															
Release of heavy metals (EN 12149-A)	Anitimony < 0.1 mg/kg			Thermal resistance "EN 12524" or "EN12667"		NPD																													
	Arcenic < 0.1 mg/kg																																		
	Barium < 0.1 mg/kg																																		
	Cadmium < 0.3 mg/kg																																		
	Chromium < 0.1 mg/kg																																		
Lead < 0.5 mg/kg																																			
Mercury < 0.1 mg/kg																																			
Selenium < 1.0 mg/kg																																			
* NPD: No Performance Declared																																			
Signed for and behalf of the manufacturer or authorised representative by: <div style="text-align: right; margin-top: 20px;"> </div>																																			
29-Jan-20		Philippe Desart		Managing Director																															