

# Declaration of Performance

DoP-CPR- 19-3630

<b>1. Unique identification code of the product, product type or product family:</b> <b>Collection:</b> VELVETEEN <b>Type:</b> 04A  <b>Designs:</b> <b>References:</b> Twirl 87000 - 87004 Tetra 87010 - 87014 Vector 87020 - 87024 Ridge 87030 - 87034																																												
<b>2. Identification of the product:</b> <b>Type, batch or serial number:</b> See packing label																																												
<b>3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15102:2007+A1:2011: Wallcovering for decorative use</b>																																												
<b>4. Name and contact address of the manufacturer:</b> <div style="float: right; text-align: right;">                     Arte NV                      Industriezone "De Waerde"                      Senator A. Jeurissenlaan 1210                      BE-3520 Zonhoven                      T +32 (0) 11 81 93 00                      F +32 (0) 11 81 93 01                      info.belgium@arte-international.com                 </div>																																												
<b>5. Name and contact address of authorised representative (distributor, importer):</b> Not applicable																																												
<b>6. System of assessment and verification of constancy of performance:</b> System 3																																												
<b>7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s):</b>  Certification report Centexbel : 19-2193																																												
<b>8. Declared performance:</b> <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width:25%;">Essential Characteristic</th> <th style="width:20%;">Performance</th> <th style="width:10%;">Harmonised technical specification</th> <th style="width:25%;">Essential Characteristic</th> <th style="width:10%;">Performance</th> <th style="width:10%;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td><b>C-s2,d0</b></td> <td rowspan="8" style="text-align: center; vertical-align: middle;">EN 15102:2007 A1:2011</td> <td rowspan="2">Release of vinyl chloride monomer EN 12149-B</td> <td rowspan="2" style="text-align: center; vertical-align: middle;">&lt; 0.2 mg/kg</td> <td rowspan="8" style="text-align: center; vertical-align: middle;">EN 15102:2007 A1: 2011</td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td style="text-align: center;">&lt; 120 mg / kg</td> </tr> <tr> <td rowspan="6">Release of heavy metals (EN 12149-A)</td> <td>Anitimony</td> <td style="text-align: center;">&lt; 0.1 mg/kg</td> <td rowspan="3">Sound absorption ISO 354</td> <td rowspan="3" style="text-align: center; vertical-align: middle;">NPD</td> </tr> <tr> <td>Arcenic</td> <td style="text-align: center;">&lt; 0.1 mg/kg</td> </tr> <tr> <td>Barium</td> <td style="text-align: center;">&lt; 0.1 mg/kg</td> </tr> <tr> <td>Cadmium</td> <td style="text-align: center;">&lt; 0.3 mg/kg</td> <td rowspan="3">Thermal resistance "EN 12524" or "EN12667"</td> <td rowspan="3" style="text-align: center; vertical-align: middle;">NPD</td> </tr> <tr> <td>Chromium</td> <td style="text-align: center;">&lt; 0.1 mg/kg</td> </tr> <tr> <td>Lead</td> <td style="text-align: center;">&lt; 0.5 mg/kg</td> </tr> <tr> <td>Mercury</td> <td style="text-align: center;">&lt; 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Selenium</td> <td style="text-align: center;">&lt; 1.0 mg/kg</td> <td></td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification	Reaction to fire EN 13501-1	<b>C-s2,d0</b>	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg	Release of heavy metals (EN 12149-A)	Anitimony	< 0.1 mg/kg	Sound absorption ISO 354	NPD	Arcenic	< 0.1 mg/kg	Barium	< 0.1 mg/kg	Cadmium	< 0.3 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD	Chromium	< 0.1 mg/kg	Lead	< 0.5 mg/kg	Mercury	< 0.1 mg/kg			Selenium	< 1.0 mg/kg		
Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification																																							
Reaction to fire EN 13501-1	<b>C-s2,d0</b>	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																																							
Release of formaldehyde EN 12149-C	< 120 mg / kg																																											
Release of heavy metals (EN 12149-A)	Anitimony		< 0.1 mg/kg	Sound absorption ISO 354		NPD																																						
	Arcenic		< 0.1 mg/kg																																									
	Barium		< 0.1 mg/kg																																									
	Cadmium		< 0.3 mg/kg	Thermal resistance "EN 12524" or "EN12667"		NPD																																						
	Chromium		< 0.1 mg/kg																																									
	Lead		< 0.5 mg/kg																																									
Mercury	< 0.1 mg/kg																																											
Selenium	< 1.0 mg/kg																																											
* NPD: No Performance Declared																																												
Signed for and behalf of the manufacturer or authorised representative by: <div style="text-align: right; margin-top: 20px;">   <b>Managing Director</b> </div>																																												
27-Mar-26		Philippe Desart		Managing Director																																								