



# Declaration of Performance

DoP-CPR- 100003000025-27880

<b>1. Unique identification code of the product, product type or product family:</b>			
<b>Collection:</b>	Luster	<b>Type:</b>	08
<b>Designs:</b>		<b>References:</b>	
Perula	Abalone	70300 - 70303	70320 - 70323
Lucea	Cornice	70310 - 70313	70330 - 70333

<b>2. Identification of the product:</b>
<b>Type, batch or serial number:</b>
See packing label

**3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15101-1 Wallcovering for decorative use**

<b>4. Name and contact address of the manufacturer:</b>	Arte NV Industriezone "De Waerde" Senator A. Jeurissenlaan 1210 BE-3520 Zonhoven T +32 (0) 11 81 93 00 F +32 (0) 11 81 93 01 info.belgium@arte-international.com
---------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>5. Name and contact address of authorised representative (distributor, importer):</b>	Not applicable
------------------------------------------------------------------------------------------	----------------


<b>6. System of assessment and verification of constancy of performance:</b>	System 3
------------------------------------------------------------------------------	----------

<b>7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s):</b>
Certification report Centexbel : 21/637

<b>8. Declared performance:</b>						
Essential Characteristic	Performance	Harmonised technical	Essential Characteristic	Performance	Harmonised technical	
Reaction to fire EN 13501-1	D-s1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	
Release of formaldehyde EN 12149-C	< 120 mg / kg					
Release of heavy metals (EN 12149-A)	Anitimony		< 0.1 mg/kg	Sound absorption ISO 354		NPD
	Arcenic		< 0.1 mg/kg			
	Barium		< 0.1 mg/kg			
	Cadmium		< 0.3 mg/kg	Thermal resistance "EN 12524" or "EN12667"		NPD
	Chromium		< 0.1 mg/kg			
Lead	< 0.5 mg/kg					
Mercury	< 0.1 mg/kg					
Selenium	< 1.0 mg/kg					

\* NPD: No Performance Declared

Signed for and behalf of the manufacturer or authorised representative by:

2-Apr-26 Philippe Desart  Managing Director